LETTER

Design of Optimal Noise Hazard Control Strategy With Budget Constraint

Mohammad Reza Monazzam

School of Public Health, Tehran University of Medical Sciences, Tehran, Iran

Samaneh Momen Bellah Fard

Science and Research Branch, Islamic Azad University, Tehran, Iran

We have read Asawarungsaengkul and Nanthavanij's article carefully [1]. It says that for engineering controls only controlling at the machine and controlling along the path were considered. However, one of the most successful engineering ways to abate noise pollution is control at source using machines with lower levels of sound pollution or machines with noise control tools [2, 3, 4, 5]. This is different from when the enclosure or silencer is attached to the machine by the engineer. The common example of this is substitution of hydraulic systems in compressors with pneumatic systems. Although the price of a machine with lower noise pollution is higher than of one with higher noise levels, the price would be justified. In this article another cost-based model, which should be considered in the engineering approach, is implementation of machines with lower noise levels compared with higher noise levels.

Another point in this survey is that Occupational Safety and Health Administration (OSHA) [6] is used as a noise conservation program. The American Conference of Governmental Industrial Hygienists (ACGIH), which is used in most occupational research [7, 8, 9, 10], with its threshold limit value (TLV) of 85 dB(*A*) for an 8-h exposure is more protective for workers. It is recommended to use the ACGIH standard where the noise levels should not exceed 85 dB(*A*) instead of the OSHA standard with 90 dB(*A*) [11]. Moreover, the formulae for the combined noise level at location *j* can also be shortened. Hence, they should be revised as

$$\bar{L}_j = 10 \log\left[10^{\frac{L_{ab}}{10}} + \sum_{t=1}^{q} \frac{10^{\frac{L_t}{10}}}{d_{tj}^2} \right], \qquad (1)$$

$$w_j = \frac{1}{p} \times 2^{\left(\frac{\bar{L}j - 85}{5}\right)}, \qquad (2)$$

$$w_j = 10\left[\log_{10}\left\{ \sum_{k \in S} w_k \right\} \right] + 85. \qquad (3)$$

The variables in the proposed equations remain the same as in the original article.

REFERENCES

1. Asawarungsaengkul K, Nanthavanij S. Design of optimal noise hazard control strategy with budget constraint. International Journal of Occupational Safety and Ergonomics (JOSE). 2006;12(4): 355–67. Retrieved September 22, 2011, from: http://www.ciop.pl/19584

Correspondence should be sent to Mohammad Reza Monazzam, Occupational Hygiene Department, School of Public Health, Tehran University of Medical Sciences, Ghods Street, Tehran, Iran. P.O. Box: 14155-6446. E-mail: <mmonazzam@gmail.com>.

2. Sams G, Jordan J. Designing low noise burners inside firetubes. Appl Acoust. 1997; 51(2):121–39 (DOI:10.1016/S0003-682X(96) 00054-0).

3. Wonnacott EJ. Lower exhaust noise from better silencer design techniques. J Sound Vib. 1974;37(1):17–26 (DOI:10.1016/S0022-460X(74)80054-4).

4. Kim T, Lee S, Kim H, Lee S. Design of low noise airfoil with high aerodynamic performance for use on small wind turbines. Science China Technological Sciences. 2010;53(1):75–9 (DOI:10.1007/s11431-009-0415-7).

5. Chaja P, Koronowicz T. Towards the design of low noise level wind turbines. Task Quarterly. 2010;13(4):393–401. Retrieved September 22, 2011, from: http://www.task.gda.pl/files/quart/TQ2009/04/tq413o-g.pdf

6. Occupational Safety and Health Administration. Occupational noise exposure: hearing conservation amendment. Fed Reg. 1983;48: 9738–85.

7. Ahmed HO, Dennis JH, Ballal SG. The accuracy of self-reported high noise exposure level and hearing loss in a working population in Eastern Saudia Arabia. Int J Hyg Environ Health. 2004; 207(3):227–34.

8. Shahna FG. Noise induces hearing loss and its relationship with dose and exposure length. The Journal of Qazvin University of Medical Sciences. 2006;10(1):84–8. In Persian, with an abstract in English. Retrieved September 22, 2011, from: http://jqums.hbi.ir/browse.php?mag_id=4&slc_lang=en&sid=1

9. Moshe S, Frenkel A, Hager M, Skulsky M, Sulkis J, Himelfarbe M. Effects of occupational exposure to mercury or chlorinated hydrocarbons on the auditory pathway. Noise Health. 2002;4(16):71–7.

10. D'Elia V, Lodi V, Naldi M, Gherardi G, Violante FS, Bonparola M, et al. Gardening work and heavy metals in urban environment. Arh hig rada toksikol. 1999;50(2):163–70. Retrieved September 22, 2011, from: http://hrcak.srce.hr/index.php?show=clanak&id_clanak_jezik=4598

11. Barron RF. Industrial noise control and acoustics. New York, NY, USA: Dekker; 2003.